PHYSICAL TESTING REPORT





Tudor Roof Tile Company Limited Denge Marsh Road Lydd Kent TN29 9JH

FAO: Mr. Paul Lythgoe				
-	TRT Handmade Various Colours	6		
Your Reference:	Plain&Peg			
Lucideon Reference: (152667)-14945				
Date Reported:	20-Jul-2015	Order Number:	PjL010715	
Date Logged:	03-Jul-2015	Date(s) of Test(s):	17-Jul-2015 to 17-Jul-2015	
Determination of Flexural Strength				
BS EN 538: 1994: Clay Roofing Tiles for Discontinuous Laying				

	Flexural Strength	
No.	kN	
1	1.05	
2	1.41	
3	1.15	
4	0.94	
5	0.94	
6	1.08	
7	1.42	
8	1.65	
9	1.61	
10	0.99	
Mean	1.22	

Span: 163 mm

Does the sample comply with the BSEN1304: 2005 Clause 4.4.2? Yes

Opinions and interpretations expressed herein are outside the scope of UKAS Accreditation.

End of Test Report



Author

This report is issued in accordance with the Conditions of Business of Lucideon Limited and relates only to the sample(s) tested. No responsibility is taken for the accuracy of the sampling unless this is done under our own supervision. This report shall not be reproduced in part without the written approval of Lucideon Limited, nor used in any way as to lead to misrepresentation of the results or their implications.

Lucideon Limited Queens Road, Penkhull Stoke-on-Trent Staffordshire ST4 7LQ

Page 1 of 1

T +44 (0)1782 764428 enquiries@lucideon.com www.lucideon.com