

Outstanding in Their Field



English Handmade Clay Tiles
300 million years in the making

Tudor Roof Tile Co. Limited

Located on the Romney Marsh in Kent, using traditional production skills, Tudor's double cambered clay roof tiles offer a link with the past. They are particularly suitable for use in architecturally and aesthetically sensitive areas.

Combining the natural properties of clay, sand facing and individualised hand making, gives Tudor tiles their 'antique' variation.

Starting with natural clay formed over 300 million years ago, each tile is individually sand faced, shaped, trimmed and nail holes inserted, then placed onto specially shaped drying trays. Each stage of production is done by hand.

Each tile then undergoes a lengthy drying process before being fired to over 1000°C. Quality inspection and packaging complete the process.

Tudor's characterful sand faced plain and peg tiles have an instant aged look which is consistent with the historic clay tiles that adorn many of Britain's ancient buildings.

Recommended by conservationists and planners when looking for 'like for like' handmade replacements. New build property owners increasingly turn to Tudor's tiles in order to add property value whilst remaining 'in keeping' with roof scapes in the surrounding area.

The lifelong quality of each tile continues to meet current changing weather conditions, using a state of the art computer controlled firing kiln which ensures all tiles are able to meet and exceed CE marking standard BS:EN 1304.

Tudor Roof Tiles - Quintessentially English

Tudor tiles are individually handmade at their factory in Kent, using skills honed and developed even before Shakespeare's time.

Tudor's kiln continually fires Tudor tiles, 24 hours a day, 7 days a week to ensure consistency and eliminate batch discrepancies.

Tudor tiles give you real peace of mind knowing that each tile comes with a 30 year guarantee of durability (unlike reclaimed tiles).

Tudor have a wide range of colours achieved with locally sourced sands from quarries around the country.

Tudor Roof Tiles are notably less expensive than other premium brands.



Home Page

where quality is important not imported



Photo Library



Technical Specifications

DIMENSIONS	(metric (mm))	(Imperial (inches))
(variable to avoid straight lines on roof)		
Plain Tiles (nibbed)	265 x 165	10.5 x 6.5
Plain Peg Tiles	255 x 160	10 x 6
Ornamentals	265 x 165	10.5 x 6.5
Oast Tapers	255 x 150 reducing to 120mm or 85mm (Two Tapers, Wide & Narrow)	
Fittings		
Ridges - all types	300 Long	12 Long
External & Internal Angles (90 degree)	265 Long	10.5 Long
Gauge (maximum)		
Plain Tile	100	4
Plain Peg	95	3.75
Roof Pitch		
BS5534:2014 Recommended Minimum - 40°		
Covering Capacity		
Plain Tile	60 Tiles / metre ²	
Plain Peg Tile	66 Tiles / metre ²	
Laid Weight (Average)		
Plain Tile	75kg / metre ²	15.36lbs / feet ²
Plain Peg Tile	75.9kg / metre ²	15.55lbs / feet ²
Weight		
per 1000 Plain Tiles - 1.25 Tonnes average		E & O.E

Full technical specifications and the product durability guarantee are downloadable from our website.



Site Map

Our tiles are tested to comply with:-

CE BS EN 538 for flexural strength.
 BS EN 539-1 for water impermeability.
 BS EN 539-2 for frost resistance.
All above are contained in the CE Marking standard EN 1304



Medium Antique



Dark Antique



Weathered Earth



Jubilee



Red Antique



Sussex Brown



Russet Brown



Sussex Red



Rustic Red



Rural Grey

Tudor Roof Tile Co. Limited
 Dengemarsh Road, Lydd, Kent TN29 9JH
www.tudorrooftiles.co.uk

Call: 01797 320202
 email: info@tudorrooftiles.co.uk